

caratteristiche

50 Hz / 1500 rpm

	1 FASE 50Hz	IS7	IS9	IS12	IS13.1	
potenza A.C. a.c. output / puissance a.c. / potencia / Leistung	115-230V max. cont.	6,7 kW 6,2 kW	9 kW 8,2 kW	11,2 kW 10,2 kW	13,1 kW 12,3 kW	
frequenza frequency / frequence / frecuencia / frequenz	Hz	50	50	50	50	
motore engine / moteur / motor / Antriebsmotor		YANMAR 3TNV76	YANMAR 3TNV82	YANMAR 3TNV88	YANMAR 3TNV84T	
iniezione injection system / système d'injection inyección / Einspritzung		indiretta / indirect indirecte / indirecta indirekt	diretta / direct / directe / directa / Direkt			
raffreddamento cooling system / refroidissement Enfriamiento / Kühlung		intercooler W/A - W/W				
cilindrata displacement / cylindrée / cilindrada / Hubraum	c.c. n°	1116 3	1330 3	1642 3	1500 3	
potenza max max power / puissance maxi. potencia máx / max. Leistung	hp	12,5	15,4	18,4	19,1	
giri/min r.p.m. / tours/min / vueltas/min / Drehzahl u/min		1500	1500	1500	1500	
regolatore di giri speed governor / regulateur de tours regulación de la vueltas / Drehzahlregler		meccanico / mechanical / mécanique / mecanico / Mechanisch				
consumo carburante a 4/4 del carico fuel consumption 4/4 load consommation de carburant 4/4 charge consumo de combustible 4/4 carga Kraftstoffverbrauch bei 4/4 der Belastung	L/h	2,3	3,2	4	4,3	
dimensioni size / dimensions / dimensiones / Maße	m m	L	760	837	985	985
		W	530	568	585	585
		H	625	688	730	730
peso weight / poids / masa / Gewicht	kg	230	295	344	390	
pressione acustica (a 7 m.) acoustic pressure (at 7 m.) pression acoustique (à 7 m.) presión acústica (a 7 m.) Schalldruck (bei 7 m.)	Lp(A) dB(A)	49	49	50	52	

mase
GENERATORS

IS 7



50 Hz / 1500 rpm

specifications / caractéristiques / especificaciones / Spezifikation

		1 FASE 50Hz	IS 16	IS 20.1	IS 24	IS 27
potenza A.C. a.c. output / puissance a.c. / potencia / Leistung		115-230V max. cont.	15,3 kW 13,9 kW	20,1 kW 18,7 kW	26 kW 24 kW	29 kW 27 kW
frequenza frequency / frequence / frecuencia / frequenz		Hz	50	50	50	50
motore engine / moteur / motor / Antriebsmotor			YANMAR 4TNV88	YANMAR 4TNV84T	YANMAR 4TNV98	YANMAR 4TNV98
iniezione injection system / système d'injection inyección / Einspritzung			diretta / direct / directe / directa / Direkt			
raffreddamento cooling system / refroidissement			intercooler W/A - W/W			
cilindrata displacement / cylindrée / cilindrada / Hubraum		c.c. n°	2190 4	1995 4	3319 4	3319 4
potenza max max power / puissance maxi. potencia máx / max. Leistung		hp	24,5	29,3	47	47
giri/min r.p.m. / tours/min / vueltas/min / Drehzahl u/min			1500	1500	1500	1500
regolatore di giri speed governor / regulateur de tours regulación de la vueltas / Drehzahlregler			meccanico / mechanical / mécanique / mecanico / Mechanisch			
consumo carburante a 4/4 del carico fuel consumption 4/4 load consommation de carburant 4/4 charge consumo de combustible 4/4 carga Kraftstoffverbrauch bei 4/4 der Belastung		L/h	5,6	6,2	7,6	10,8
dimensioni size / dimensions / dimensiones / Maße		m m				
		L	1115	1115	1225	1225
		W	585	585	630	630
		H	730	730	830	830
peso weight / poids / masa / Gewicht		kg	400	465	625	625
pressione acustica (a 7 m.) acoustic pressure (at 7 m.) pression acoustique (à 7 m.) presión acústica (a 7 m.) Schalldruck (bei 7 m.)		Lp(A) dB(A)	50	52	54	54

mase
GENERATOR

IS 27



11